

HEAD OFFICE:


8 PROP STREET, SELBY EXT. 11, JOHANNESBURG, 2001
PO BOX 6014, JOHANNESBURG, 2000
TEL: +27 (11)493 7956/9 - 493 7960/1/5 | FAX: +27 (11) 493 0260
EMAIL: ROPECONS@ROPECON.CO.ZA - WWW.ROPECON.CO.ZA

DURBAN:

14C BOUGAINVILLEA RD
QUEENSBOROUGH
TEL: +27 (31) 463 1687
FAX: +27 (31) 463 1018

CAPE TOWN:

4B BUTSKOP RD
BLACKHEATH
TEL: +27 (21) 905 9465
FAX: +27 (21) 905 1980



Application: Haulage Ropes, Choker Ropes, Crane Ropes, General Engineering Ropes, Rotary drilling ropes, Hoist Ropes

Characteristics: Resistant to abrasion and crushing; Medium fatigue resistance

DIAMETER		Steel Wire Rope Section mm ²	Steel Wire Rope Weight Kg / m	MBL 1770 MPa KN
Steel wire Rope mm	Wire Dia. mm			
6	-	13.82	0.1281	21.02
8	0.65	24.57	0.2278	37.38
9	0.74	31.10	0.2883	47.31
10	0.82	38.40	0.3559	58.41
11	0.90	46.46	0.4307	70.67
12	0.98	55.29	0.5126	84.11
13	1.06	64.89	0.6016	98.71
14	1.14	75.26	0.6977	114.48
16	1.30	98.30	0.9113	149.52
18	1.46	124.41	1.1534	189.24
19	1.53	138.62	1.2851	210.86
20	1.62	153.60	1.4239	233.64
22	1.77	185.85	1.7230	282.70