

HEAD OFFICE:


8 PROP STREET, SELBY EXT. 11, JOHANNESBURG, 2001
 PO BOX 6014, JOHANNESBURG, 2000
 TEL: +27 (11)493 7956/9 - 493 7960/1/5 | FAX: +27 (11) 493 0260
 EMAIL: ROPECONS@ROPECON.CO.ZA - WWW.ROPECON.CO.ZA

DURBAN:

14C BOUGAINVILLEA RD
 QUEENSBOROUGH
 TEL: +27 (31) 463 1687
 FAX: +27 (31) 463 1018

CAPE TOWN:

4B BUTSKOP RD
 BLACKHEATH
 TEL: +27 (21) 905 9465
 FAX: +27 (21) 905 1980



Application: For Cranes, Hoists, general engineering, Hawser and mooring lines

Characteristics: fibre core for flexibility; galvanized for corrosion resistance

DIAMETER		Steel Wire Rope Section mm ²	Steel Wire Rope Weight Kg / m	MBL 1770 MPa KN
Steel wire Rope mm	Wire Dia. mm			
10	0.46	35.69	0.3460	52.21
11	0.51	43.19	0.4186	63.18
12	0.55	51.40	0.4982	75.18
13	0.60	60.33	0.5847	88.24
14	0.64	69.97	0.6781	102.34
16	0.74	91.39	0.8857	133.67
18	0.82	115.66	1.1210	169.17
19	0.88	128.87	1.2490	188.49
20	0.92	142.79	1.3840	208.85
22	1.02	172.78	1.6749	252.72
24	1.10	205.63	1.9929	300.75
26	1.20	241.33	2.3389	352.97
28	1.28	279.88	2.7126	409.36
30	1.38	321.29	3.1140	469.93
32	1.46	365.56	3.5430	534.68