



**HEAD OFFICE:**


8 PROP STREET, SELBY EXT. 11, JOHANNESBURG, 2001  
 PO BOX 6014, JOHANNESBURG, 2000  
 TEL: +27 (11)493 7956/9 - 493 7960/1/5 | FAX: +27 (11) 493 0260  
 EMAIL: ROPECONS@ROPECON.CO.ZA - WWW.ROPECON.CO.ZA

**DURBAN:**

14C BOUGAINVILLEA RD  
 QUEENSBOROUGH  
 TEL: +27 (31) 463 1687  
 FAX: +27 (31) 463 1018

**CAPE TOWN:**

4B BUTSKOP RD  
 BLACKHEATH  
 TEL: +27 (21) 905 9465  
 FAX: +27 (21) 905 1980



**For: Dragging and Hauling, Staying ,Tramways and sand lines**

**Characteristics :Low Stretch, Excellent abrasion resistance, less bending fatigue resistance**

DIAMETER		Steel Wire Rope Section mm <sup>2</sup>	Steel Wire Rope Weight Kg / m	MBL 1770 MPa KN
Steel wire Rope mm	Wire Dia. mm			
6	0.64	17	0.14	26
7	0.74	23	0.19	35
8	0.86	30	0.25	47
9	0.96	38	0.32	59
10	1.06	46	0.39	72
11	1.18	57	0.48	89
12	1.28	67	0.57	105
13	1.38	78	0.66	121
14	1.48	90	0.76	140
15	1.59	104	0.87	161
16	1.71	120	1.01	186
17	1.80	134	1.13	208
18	1.92	151	1.27	235
19	2.01	166	1.40	258
20	2.12	184	1.56	286
21	2.22	203	1.71	315
22	2.33	223	1.88	346