

# POLYESTER



## Australia

164 Bannister Rd  
Canning Vale  
WA 6155

## South Africa

8 Prop Street  
Selby Ext.11  
Johannesburg

POLYESTER WEB SLING  
& ROUND SLING  
RATCHET STRAPS



# POLYESTER

# EN ENDLESS WEBBING



## Endless Webbing Sling EN1492-1

- 100% high tenacity polyester
- Single Ply
- Low elongation
- Each black stripe is equal to 1 ton capacity
- Manufactured in various lengths and made to order
- Safety factor available : 5 to 1 / 6 to 1 / 7 to 1 and 8 to 1
- Complies with EN1492-1



**LOADSET**  
SAFE LIFTING - SECURE LASHING - GO

### SINGLE WEBBING SLING

### DOUBLE WEBBING SLING



COLOUR CODE	WEBBING WIDTH	VERTICAL WLL kg	CHOKE WLL kg	BASKET WLL kg	SINGLE WEBBING SLING				DOUBLE WEBBING SLING			
					7'-45"	45'-60"	UP TO 45'	45'-60"	STRAIGHT 45'	CHOKE 45'	STRAIGHT 45'-60"	CHOKE 45'-60"
VIOLET	25/30	1000	800	2000	1400	1000	700	500	1400	1120	1000	800
GREEN	50/60	2000	1600	4000	2800	2000	1400	1000	2800	2240	2000	1600
YELLOW	75/90	3000	2400	6000	4200	3000	2100	1500	4200	3360	3000	2400
GREY	100/120	4000	3200	8000	5600	4000	2800	2000	5600	4480	4000	3200
RED	125/150	5000	4000	10000	7000	5000	3500	2500	7000	5600	5000	4000
BROWN	150/180	6000	4800	12000	8400	6000	4200	3000	5400	6720	6000	4800
BLUE	200/240	8000	6400	16000	11200	8000	5600	4000	11200	8960	8000	6400
ORANGE	250/300	10000	8000	20000	14000	10000	7000	5000	14000	11200	10000	8000

# WEBBING SLING



## Flat Webbing Sling EN1492-1 / AS1353

- 100% high tenacity polyester
- Single or Double Ply
- Low elongation
- With reinforced lifting eyes
- Manufactured in various lengths and made to order
- Extra durable WLL tag with clear protective sleeve fitted
- Safety factor available : 7 : 1 and 8 : 1
- Complies with EN1492-1 or AS1353

**LOADSET**  
SAFE LIFTING - SECURE LASHING



M = 1.0



M = 0.8



M = 2.0



M = 1.9



M = 1.7



M = 1.4



M = 1.0



M = 1.7



M = 1.4

COLOUR CODE	VERTICAL WLL kg	CHOKE WLL kg	BASKET 3 WLL kg	30° WLL kg	60° WLL kg	90° WLL kg	120° WLL kg	60° WLL kg	60° CHOKE WLL kg
VIOLET	1000	800	2000	1900	1700	1400	1000	1700	1400
GREEN	2000	1600	4000	3800	3400	2800	2000	3400	2800
YELLOW	3000	2400	6000	5700	5100	4200	3000	5100	4200
GREY	4000	3200	8000	7600	6800	5600	4000	6800	5600
RED	5000	4000	10000	9500	8500	7000	5000	8500	7000
BROWN	6000	4800	12000	11400	10200	8400	6000	10200	8400
BLUE	8000	6400	16000	15200	13800	11200	8000	13800	11072
ORANGE	10000	8000	20000	19000	17000	14000	10000	17000	1400
ORANGE	12000	9600	24000	22800	20400	16800	12000	20400	16800

Note ~ The maximum WLL is determined by the sling angle.  
The maximum WLL upto 30 tonnes available upon request.

# ROUND SLING



**LOADSET**  
SAFE LIFTING - SECURE LASHING



LOADSET Roundslings are manufactured from the highest quality materials.

Roundslings are the ideal solution for lifting and rigging loads of all shapes and sizes.

LOADSET Roundslings are lightweight, super strong and robust yet delicate on loads.

With capacities available from 1T to 1000T WLL LOADSET roundslings can lift almost anything.

## Round Sling EN1492-2 / AS4497

- 100% high tenacity polyester of out sleeve and inner core
- Single or Double Ply
- Low elongation
- Each black stripe is equal to 1 ton capacity
- Manufactured in various lengths and made to order
- Extra durable WLL tag with clear protective sleeve fitted
- Safety factor 7 : 1
- Complies with EN1492-2 or AS4497



M = 1.0



M = 0.8



M = 2.0



M = 1.9



M = 1.7



M = 1.4



M = 1.0



M = 1.7



M = 1.4

COLOUR CODE	VERTICAL WLL kg	CHOKE WLL kg	BASKET 3 WLL kg	30° WLL kg	60° WLL kg	90° WLL kg	120° WLL kg	60° WLL kg	60° CHOKE WLL kg
VIOLET	1000	800	2000	1900	1700	1400	1000	1700	1400
GREEN	2000	1600	4000	3800	3400	2800	2000	3400	2800
YELLOW	3000	2400	8000	5700	5100	4200	3000	5100	4200
GREY	4000	3200	8000	7600	6800	5600	4000	6800	5600
RED	5000	4000	10000	9500	8500	7000	5000	8500	7000
BROWN	6000	4800	12000	11400	10200	8400	6000	10200	8400
BLUE	8000	6400	16000	15200	13600	11200	8000	13600	11072
ORANGE	10000	8000	20000	19000	17000	14000	10000	17000	14000
ORANGE	12000	9600	24000	22800	20400	16800	12000	20400	16800
ORANGE	15000	12000	30000	29500	25500	21000	15000	25500	21000
ORANGE	20000	16000	40000	38000	34000	28000	20000	34000	28000
ORANGE	30000	24000	60000	57000	51000	52000	30000	51000	52000
ORANGE	50000	40000	100000	95000	85000	70000	50000	85000	70000

Note ~ The maximum WLL is determined by the sling angle.  
The maximum WLL upto 1000 tonnes available upon request.

